

PRODUCT SPECIFICATIONS, INSTALLATION INFORMATION, WARRANTY

- 01-380-600 Exhaust Fan – Multi-Mount**
- 01-380-570 Intake Fan – Multi-Mount**
- 01-380-570L Intake Fan – Multi-Mount (With Louver)**

Specifications:

- Output: 225 CFM
- Nominal: 1.1A at 12V DC
- Usage: 15 Watts
- Noise: 49 dB
- Power Jack: Use Fan Connector Wire with Quick Splice Connectors or 12V AC Adapter (01-175-032).



Front & Back View
Before Mount

The ATMOX Multi-Mount Fans are designed for various configurations. Once setup has been determined, follow one of these assembly steps. For mounting instructions, refer to specific instructions of plate or roof cap.

Assembly Steps for Mounting Plates:

1. Find the supplied screws, washers, lock washers and wing nuts to be used to attach fan to plate.
2. Insert the 4 screws into the mounting plate. Insert the screws on the side of the plate that has countersunk screw holes (side of plate with the label). Lay on surface with screws pointed up.
3. Align the fan onto the plate. The sticker and jack on the fan should be at the top of the plate.
4. Attach screws to plate by using the flat washer and then the lock washer over the screw. Use the wingnut to tighten and hold screw in place.
5. Repeat step 4 for all four corners of fan.






Assembly Steps for Roof Caps:

1. Turn roof cap over and align the straight and rounded corners.
2. Push the fan housing and click into place.



Power Options:

ATMOX Controls	ATMOX Power Supply	AC Adapter Using Standard Outlet
<p>Use Fan Connector Wire with Quick Splice Connectors Item: 01-175-510 (included with fan)</p> <ul style="list-style-type: none"> • ATMOX Controls trigger fans to come on and off to improve conditions. • One electrical outlet needed for control box to power all fans. • Different ATMOX fans can be combined up to 150 watts or 10 of the 225 CFM fans. Note usage of fans used. • Fans receive power and signal through low voltage wire. Recommend 14/2 gauge. (Item: 03-200-100) • Fan Connector Wire plugs into jack on side of fan. See instructions in ATMOX Control Installation Guide for more information on wiring. 	<p>Use Fan Connector Wire with Quick Splice Connectors Item: 01-175-510 (included with fan)</p> <ul style="list-style-type: none"> • Power Supply runs continuously unless triggered by some type of control. • One electrical outlet needed for power supply to power all fans. • Different ATMOX fans can be combined up to 150 watts or 10 of the 225 CFM fans. Note usage of fans used. • Fans receive power through low voltage wire. Recommend 14/2 gauge. (Item: 03-200-100) • Fan Connector Wire plugs into jack on side of fan. See instructions in ATMOX Power Supply Installation Guide for more information on wiring. 	<p>Use 12V AC Adapter Item: 01-175-032 (AC Adapters not included – sold separately)</p> <ul style="list-style-type: none"> • Use one electrical outlet for each individual fan. • Outlet must be within 6 feet of fan location. • Fan will run continuously unless triggered by some type of control. • AC Adapter plugs directly into jack on side of fan. 

LIMITED THREE-YEAR WARRANTY

When installed, operated, used and maintained as intended in residential applications and according to the instructions supplied with ATMOX products, ATMOX warrants its products for a period of 3-years from the date of purchase against any defects in material and workmanship. The products covered by this warranty include the control boxes, fans, sensors and wiring manufactured by ATMOX. ATMOX will repair or replace, at ATMOX’s option, any ATMOX product or component found to be defective within the 3-year warranty period.

ATMOX products are designed to improve conditions in the crawlspace, basement or attic, yet are limited by atmospheric and natural conditions over which ATMOX has no control and which are not covered by this warranty. ATMOX products are not warranted against damage caused by electrical surges, fire or other casualty, vandalism, or acts of God (including lightning strikes and floods). This warranty does not make representations regarding mold, insects, termites, water, rot, electrical, HVAC, roof, framing, foundation, floors, drywall, gutters, ice dams or other problems that may occur in a house structure. The warranty does not include any costs of removal or reinstallation.

Third-party products by other manufacturers sold by ATMOX (such as dehumidifiers) are not covered by this warranty but may be covered under separate warranties by the product’s manufacturer. Purchaser should contact third party manufacturers for warranty claims and coverage of third-party products not manufactured by ATMOX.

ATMOX INC’S LIABILITY UNDER THIS LIMITED WARRANTY IS STRICTLY LIMITED TO REPAIR OR REPLACEMENT OF DEFECTIVE ATMOX PRODUCTS. OTHER THAN THE WARRANTIES EXPRESSLY DESCRIBED HEREIN, ATMOX DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ATMOX WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Some states do not allow certain limitations and exclusions of warranty, so these exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.