



## SPECIFICATIONS

### ATMOX INTERNAL FAN – JOIST MOUNT

01-380-202

Output:	225 CFM
Nominal:	1.1A at 12V DC
Usage:	15 Watts
Noise:	49 dB
Power:	2.1mm Jack (Center Negative)
Mount:	Use U-Bracket to mount to joist

## POWER OPTIONS



**Fan Connector Wire with Quick Splice Connectors** (Included)  
Reference the Installation Guide for low voltage wiring instructions. Jack plugs directly into fan.



**12V AC Adapter** (Sold separately – Item: 01-175-032)  
For use in standard electrical outlet within 6 feet of fan.  
Fan will run continuously. Jack plugs directly into fan.

## LIMITED THREE-YEAR WARRANTY

When installed, operated, used and maintained as intended in residential applications and according to the instructions supplied with ATMOX products, ATMOX warrants its products for a period of 3-years from the date of purchase against any defects in material and workmanship. The products covered by this warranty include the control boxes, fans, sensors and wiring manufactured by ATMOX. ATMOX will repair or replace, at ATMOX's option, any ATMOX product or component found to be defective within the 3-year warranty period.

ATMOX products are designed to improve conditions in the crawlspace, basement or attic, yet are limited by atmospheric and natural conditions over which ATMOX has no control and which are not covered by this warranty. ATMOX products are not warranted against damage caused by electrical surges, fire or other casualty, vandalism, or acts of God (including lightning strikes and floods). This warranty does not make representations regarding mold, insects, termites, water, rot, electrical, HVAC, roof, framing, foundation, floors, drywall, gutters, ice dams or other problems that may occur in a house structure. The warranty does not include any costs of removal or reinstallation.

Third-party products by other manufacturers sold by ATMOX (such as dehumidifiers) are not covered by this warranty but may be covered under separate warranties by the product's manufacturer. Purchaser should contact third party manufacturers for warranty claims and coverage of third-party products not manufactured by ATMOX.

ATMOX INC'S LIABILITY UNDER THIS LIMITED WARRANTY IS STRICTLY LIMITED TO REPAIR OR REPLACEMENT OF DEFECTIVE ATMOX PRODUCTS. OTHER THAN THE WARRANTIES EXPRESSLY DESCRIBED HEREIN, ATMOX DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ATMOX WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Some states do not allow certain limitations and exclusions of warranty, so these exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

**WARNING: Cancer and Reproductive Harm – For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**



10612-D Providence Road. #229, Charlotte, NC 28277 • 704-248-2858 • [www.atmox.com](http://www.atmox.com)

## INSTALLATION INFORMATION

### Tools Needed for Installation:

- Drill with screw bit

### Installation Steps:

1. Take U-Bracket, extension shaft (pipe) and 4 locknuts.
2. Screw 1 locknut on each end of shaft.
3. Insert shaft into U-Bracket and attach by tightening with lock nut.
4. Attach other end of shaft into opening in fan bracket and tighten with lock nut.
5. The bracket is now ready to be mounted directly to the joist in the crawlspace or attic.
6. Use screws to attach U-Bracket to both sides of the joist through the available openings. Make the bracket tight to avoid fan vibration.
7. Fan is ready for power connection.



### Optional Ducting:

- For hard-to-ventilate areas, insulated or non-insulated 8" ducting can be attached to either one or both ends of the Pipe Fan.
- Attach ducting using multiple cable ties strapped together and tightened around fan grill.

