



SPECIFICATIONS

ATMOX SUPPLIES KIT - SENSOR CABLES 01-550-900

Kit includes:

- (1) Crimping Tool for RJ11 Jacks
- (4) Extension Cables with Couplers (25')
- (100) RJ11 Plug for Stranded Flat Wire

Replacement sensor can be purchased separately.

LIMITED THREE-YEAR WARRANTY

When installed, operated, used and maintained as intended in residential applications and according to the instructions supplied with ATMOX products, ATMOX warrants its products for a period of 3-years from the date of purchase against any defects in material and workmanship. The products covered by this warranty include the control boxes, fans, sensors and wiring manufactured by ATMOX. ATMOX will repair or replace, at ATMOX's option, any ATMOX product or component found to be defective within the 3-year warranty period.

ATMOX products are designed to improve conditions in the crawlspace, basement or attic, yet are limited by atmospheric and natural conditions over which ATMOX has no control and which are not covered by this warranty. ATMOX products are not warranted against damage caused by electrical surges, fire or other casualty, vandalism, or acts of God (including lightning strikes and floods). This warranty does not make representations regarding mold, insects, termites, water, rot, electrical, HVAC, roof, framing, foundation, floors, drywall, gutters, ice dams or other problems that may occur in a house structure. The warranty does not include any costs of removal or reinstallation.

Third-party products by other manufacturers sold by ATMOX (such as dehumidifiers) are not covered by this warranty but may be covered under separate warranties by the product's manufacturer. Purchaser should contact third party manufacturers for warranty claims and coverage of third-party products not manufactured by ATMOX.

ATMOX INC'S LIABILITY UNDER THIS LIMITED WARRANTY IS STRICTLY LIMITED TO REPAIR OR REPLACEMENT OF DEFECTIVE ATMOX PRODUCTS. OTHER THAN THE WARRANTIES EXPRESSLY DESCRIBED HEREIN, ATMOX DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ATMOX WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Some states do not allow certain limitations and exclusions of warranty, so these exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

WARNING: Cancer and Reproductive Harm – For more information, go to www.P65Warnings.ca.gov



10612-D Providence Road. #229, Charlotte, NC 28277 • 704-248-2858 • www.atmox.com

INSTRUCTIONS FOR REPLACING JACKS ON RJ11 CABLES

Steps:

1. Unlock crimping tool.
2. Place end of cable under blade and make a fresh cut.
3. Place cable into the slot under front blade until it reaches the back panel.
4. Grip down and pull the cable out by stripping off the black sheathing and exposing the colored wires. Be sure not to damage or shave the colored wires when stripping the outer black sheathing of the cable.
5. Remove the small portion of the stripped cable that may remain inside of tool.
6. Insert stripped cable into jack with gold threads facing upward and **black wire to the left**.
7. Insert jack into crimping tool and firmly grip down to secure a connection. Remove cable by releasing jack.

